

DG 25 Set (604116500) Air Die Grinder
Plastic Carry Case

Order no. 604116500
EAN 4007430228918



Product may differ from Image

- For sanding/grinding, deburring, moulding/routing and engraving
- Integrated speed control
- Ergonomic, partially rubber-coated housing: cold-insulating, non-slip and low vibration for comfortable work
- Safety lever for protection against accidental start up
- Rotatable exhaust guide at the side of the housing.

Technical data**Characteristics**

Operating pressure	6.2 bar / 90 psi
Air requirement	300 l/min / 11 cfm
Maximum speed	25000 rpm
Collet chuck bore	6 mm / 0.2362 "
Weight	0.43 kg / 0.9 lbs

Vibration

Surface grinding	0.1 m/s ²
Uncertainty of measurement K	0.8 m/s ²

Noise emission

Sound pressure level	75 dB(A)
Sound power level (LwA)	87 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

EURO Plug-in nipple 1/4"
2 collets (3 mm, 6 mm)
5 mounted points each (3 mm, 6 mm)
2 open-jawed spanners (13 mm, 16 mm)
Plastic carry case
ARO/Orion Plug-in nipple 1/4"
ISO Plug-in nipple 1/4"