

HITACHI

Demolition Hammer Service Kit Application

- Purpose:** Generally speaking, Demolition Hammers are operated under extremely heavy loads and hard working conditions.
For this reason, there are several consumable parts which have a considerably shorter service life than similar parts in various other power tools. Timely and regular replacement of such parts (carbon brushes, O-rings, etc.) can significantly extend the operational service life of the Demolition Hammer. The Demolition Hammer Service Kit has been prepared to assist service centers in providing easier and less costly maintenance and repair services for our customers, and to ensure that the customer gains maximum product performance.
- Applicable Models:** H65SB3
- Contents:** Service Kit component parts for each model are listed in the table below.
The item numbers correspond to the circled numbers in exploded assembly diagrams in technical data and service manuals, and/or parts lists.

(1) H65SB3:

Item No.	Code No.	Part Name	No. Used	Application
1	323734	Nylock Hex. Socket HD. Bolt M8×40	6	Remove old bolts, and replace with new ones. Liberally coat grease (FG-6A) prior to assembly.
13	998428	O-Ring (C)	1	
14	339684	O-Ring (B)	1	Liberally coat grease (SEP-3A) prior to assembly.
16	339681	O-Ring	2	
20	370894	Mouth Washer (A)	1	
21	370893	Urethane Ring (A)	1	
24	956996	O-Ring (1AS-60)	1	
26	998414	O-Ring (A)	1	Liberally coat grease (FG-6A) prior to assembly.
31	998415	Oil Seal (A)	1	Liberally coat grease (FG-6A) prior to assembly.
47	323725	Seal Ring	1	
89	999086	Carbon Brush	1	
—	981840	Grease A (30g)	3	FG-6A: Apply 82g (2.9oz) for Crank mechanism.
—	930035	Grease (100g)	1	SEP-3A: Apply 78g (2.7oz) for Gear.