


Various options



High Pressure Washer HW1300 / HW1200

Easy pressure adjustment and Self-Priming function



Simple function type
HW1200

High function type
2-pressure selection / Hose Reel
HW1300

Eco-friendly for reduced water

High Pressure Washer	HW1300 / HW1200	
	HW1300	HW1200
Double Insulation		
Continuous rating input	1,800W	1,800W
Max Pressure	13 MPa (130 bar, 1,885 PSI)	12 MPa (120 bar, 1,740 PSI)
Max Flow Rate	450 L/h	420 L/h
Max Feed Temperature	40 °C (104 °F)	40 °C (104 °F)
High Pressure Hose Length	10 m (33 ft.)	10 m (33 ft.)
Sound Pressure Level	76 dB(A)	72 dB(A)
Vibration Level	4.86 m/s ²	4.11 m/s ²
Dimensions (L x W x H)	292x358x830 mm(11-1/2"x14-1/8"x32-3/4")	292x358x830 mm(11-1/2"x14-1/8"x32-3/4")
Net weight	12.7 kg (28.0 lbs.)	11.0 kg (24.3 lbs.)
Power supply cord	5.0 m (16.4 ft.)	5.0 m (16.4 ft.)

Standard Equipment: Trigger Gun, Vario-Power Spray Lance, Cyclone jet nozzle, Detergent Bottle, Cleaner Pin, Coupling Sleeve, High Pressure Hose 10 m, Water Hose Connector, Foam Nozzle, Connector

Items of standard equipment and specifications may vary by country or area. weight according to EPTA-Procedure 01/ver.2.1

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201802