

# 0 611 251 755 – GBH 2-26 RE

|                                    |               |
|------------------------------------|---------------|
| Material number                    | 0 611 251 755 |
| EAN                                | 3165140613606 |
| Auxiliary Handle<br>1 612 025 058  | ✓             |
| Carrying case<br>1 615 438 429     | ✓             |
| Depth stop 210 mm<br>1 613 001 009 | ✓             |



## Technical data

### Technical data

|   |   |
|---|---|
| Rated input power                               | 800 W   |
| Impact energy (according to EPTA 05/2016)       | 2.7 J   |
| Impact rate at rated speed                      | 0 – 4,000 bpm   |
| Rated speed                                     | 0 – 900 rpm   |
| Weight  | 2,7 kg  |
| Tool dimensions (width)                         | 83 mm   |
| Tool dimensions (length)                        | 377 mm  |
| Tool dimensions (height)                        | 210 mm  |
| Tool holder                                     | SDS plus  |
| Drilling diameter in concrete with core cutters | 16 mm   |
| Noise level                                     | The A-rated noise level of the power tool is typically as follows: Sound pressure level 91 dB(A); Sound power level 102 dB(A). Uncertainty K= 3 dB. |



### Drilling range

|   |           |
|---|-----------|
| Hammer drilling diameter range in concrete      | 4 – 26 mm |
| Recommended drilling diameter range in concrete | 8 – 16 mm |
| Max. drilling diameter masonry, core cutters    | 68 mm     |
| Max. drilling diameter in metal                 | 13 mm     |
| Max. drilling diameter in wood                  | 30 mm     |



## Sales information

---

### Positioning

- The sturdy tool for daily use

### User benefit

- Powerful 800-watt motor and impact force of 2.7 joules for a fast drilling rate
- Changeable toolholder
- Rotatable brush plate (equal power in forward and reverse rotation)