

# 0 601 9E0 0F6 – GDR 12 V-EC

Material number	0 601 9E0 0F6
EAN	3165140853385
2 x 2.0 Ah battery	✓
Carrying case	✓
Quick charger GAL 1230 CV	✓
1 600 A00 R44	



## Technical data

### Technical data

No-load speed (1st level)	0-1,200 rpm
No-load speed (2nd level)	0-2,600 rpm
Torque settings	2
Torque, max.	110 Nm
Impact rate	0-3,100 bpm
Impact rate (1st level)	0-2,700 bpm
Impact rate (2nd level)	0-3,100 bpm
Battery voltage	12.0 V
Tool holder	1/4" Hex Uni
Tool dimensions (width)	54 mm
Tool dimensions (length)	139 mm
Tool dimensions (height)	177 mm
Battery capacity	2,0 Ah
No-load speed	0-1,200 rpm
Weight incl. battery	0,9 kg
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 87 dB(A); Sound power level 100 dB(A). Uncertainty K= 3 dB.

### Screw diameter

Screw diameter	M 4 – M 12
----------------	------------



## Sales information

---

### Positioning

- More lifetime and higher precision while being as compact as ever

### User benefit

- 100% longer lifetime due to brushless motor technology and an optimised impact mechanism
- Greater accuracy when screwdriving: 2-stage PowerControl to prevent overtightening of small screws and a max. Torque of 110 Nm
- Longer runtime due to 2.5 Ah battery packs