

0 601 9J8 5F0 – GDS 18V-1050 H

Material number	0 601 9J8 5F0
EAN	4059952564753
2 x battery GBA 18V 5.0Ah 1 600 A00 1Z6	✓
L-BOXX 136 1 600 A01 2G0	✓
Quick charger GAL 18V-40 Professional 1 600 A01 9RJ	✓



Technical data

Description

Long version part 1 (BE)

The GDS 18V-1050 H Professional is the outstanding 3/4" impact wrench with brushless motor for the most diverse fields of application. Its BITURBO Brushless technology combines corded power with cordless freedom fully maximised for ProCORE 18V batteries. Whenever heavy-duty performance is needed, the new impact mechanism provides a tightening Torque of 1,050 Nm and breakaway torque of 1,700 m for particularly challenging working environments. The high versatility in power controlling is ensured by the 3-speed/torque settings that allow adjustments to the respective work requirements.



Long version part 2 (BE)

The main areas of GDS 18V-1050 H Professional are meal applications (M10-M24) like structural steel construction, metal assembly, pipe fitting, truck maintenance, and wood construction. It is compatible with all Bosch Professional 18 V batteries and chargers (Professional 18V system).



Tool dimensions (width)	86 mm
Tool dimensions (length)	222 mm
Tool dimensions (height)	240 mm
Battery capacity	5,0 Ah
Torque, max. (hard screwdriving applications)	1050 Nm
Battery voltage	18.0 V
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 95 dB(A); Sound power level



0 601 9J8 5F0 – GDS 18V-1050 H

106 dB(A). Uncertainty K= 5 dB.

Technical data

Torque adjustment range, min./max., 1st level	0/350 Nm
Torque adjustment range, min./max., 2nd level	0/750 Nm
Torque adjustment range, min./max., 3rd level	0/1050 Nm
No-load speed	0 rpm
No-load speed (1st level)	0 rpm
No-load speed (2nd level)	0-1,200 rpm
No-load speed (3rd level)	0-1,750 rpm
Torque settings	3
Weight excl. battery	2.9 kg
Torque, max.	1050 Nm
Impact rate	0-2,600 bpm
Impact rate (1st level)	0-1,600 bpm
Impact rate (2nd level)	0-2,400 bpm
Impact rate (3rd level)	0-2,600 bpm
Tool holder	3/4" Square
Breakaway torque, max.	1700 Nm

Screw diameter

Screw diameter	M 14 - M 24
----------------	-------------

Sales information

Positioning

- Full power at its best: 3/4" high torque impact wrench with BITURBO Brushless technology

User benefit

- Impressive power with cordless freedom thanks to ProCORE 18V batteries and brushless motor
- High performance motor with a tightening torque of 1,050 Nm and a breakaway torque of up to 1,700 Nm
- Ideal versatility and controlled power due to 3-speed/torque settings

