# 0 601 6B1 0F0 - GSA 120

| Material number   | 0 601 6B1 0F0 |
|---|---------------|
| EAN   | 3165140913126 |
| 1 x reciprocating saw blade S 1126 BEF,<br>Heavy for Metal<br>available separately as set of 5: 2 608 657 395 | ✓             |
| Cardboard box   | ✓             |
| Hex key   | ✓             |





### **Technical data**

### Technical data

| Rated input power        | 0 W  |
|--------------------------|--|
| Stroke rate at no load   | 0 – 3,000 spm  |
| Weight                   | 3,6 kg   |
| Cable length             | 3 m  |
| Saw, stroke length       | 29 mm  |
| Tool dimensions (width)  | 96 mm  |
| Tool dimensions (length) | 475 mm   |
| Tool dimensions (height) | 165 mm   |
| Noise level              | The A-rated noise level of the power tool is typically as follows: Sound pressure level 88.5 dB(A); Sound power level 99.5 dB(A). Uncertainty K= 5 dB. |



| Cutting depth in wood                           | 220 mm |
|---|--------|
| Cutting depth in steel plate                    | 20 mm  |
| Cutting depth in metal profiles and metal pipes | 20 mm  |

### Noise/vibration information

| Sound pressure level | 88.5 dB(A) |
|----------------------|------------|
| Sound power level    | 99.5 dB(A) |
| Uncertainty K        | 5 dB       |











## 0 601 6B1 0F0 - GSA 120

### **Sales information**

### **Positioning**

Cut more with the latest transmission, ultra durable reciprocating saw

#### **User benefit**

- Long lifetime
- Low-friction transmission system and optimised motor heat release extend the durability
- Powerful cutting
- The 1,200 W motor, highest power in its class makes cutting effortless
- Comfort in usage
- The combination of soft & hard materials in handle ensures a comfortable grip in any position

