0 601 6A5 080 - GSA 18V-LI C

Material number	0 601 6A5 080
EAN	6949509222077
1 x reciprocating saw blade S 922 AF, Flexible for Metal available separately as set of 2: 2 608 656 036	✓
1 x reciprocating saw blade S 922 EF, Flexible for Metal available separately as set of 2: 2 608 656 038	✓
1 x reciprocating saw blade S 922 HF, Flexible for Wood + Metal available separately as set of 2: 2 608 656 039	✓
Cardboard box	√
Inlay for L-BOXX 136	✓



Technical data

Technical data

Cutting depth in wood	200 mm
Cutting depth in metal profiles and metal pipes	100 mm
Stroke lengths	21 mm
Weight excl. battery	2 kg
Battery voltage	18.0 V
Stroke rate (1st gear / 2nd gear)	0 - 3,050 spm
Tool dimensions (width)	78 mm
Tool dimensions (length)	367 mm
Tool dimensions (height)	177 mm
Weight incl. battery	2,5 kg
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 82 dB(A); Sound power level 93 dB(A). Uncertainty K= 5 dB.









Noise/vibration information

Sound pressure level	82 dB(A)
Sound power level	93 dB(A)
Uncertainty K	5 dB

Sales information

Positioning

Compact powerhouse with low vibration

User benefit

- Compact design for versatile also one-handed and overhead use
- Lowest vibration levels ensure comfortable use
- A fast sawing rate and long runtime thanks to powerful motor and high-endurance batteries



