

0 601 217 1F3 – GSB 13 RE

Material number	0 601 217 1F3
EAN	3165140548106
Auxiliary handle 1 602 025 024	✓
Depth stop 210 mm 1 613 001 010	✓
Keyed chuck 13 mm 2 608 571 079	✓



Technical data

Description

Long version part 1 (BE)

The GSB 13 RE Professional is a compact corded 1-gearred entry-level impact drill. Its 1.8 kg lightweight design and small housing size provide convenience in handling and manoeuvrability. It is also particularly robust, including a durable metal keyless chuck. Additionally, this impact drill delivers professional results at an optimum price performance value.

Long version part 2 (BE)

This tool is intended for drilling in concrete, stone, and masonry.

Noise level

The A-rated noise level of the power tool is typically as follows: Sound pressure level dB(A); Sound power level dB(A). Uncertainty K= dB.



Technical data

Rated input power	600 W
No-load speed, 1st gear	0 – 2,800 rpm
Power output	301 W
Weight	1.8 kg
Rated torque	1.8 Nm
Drill spindle connecting thread	1/2"-20 UNF
Chuck capacity, min./max.	1.5 – 13 mm
Tool dimensions (length)	266 mm
Tool dimensions (height)	180 mm
Impact rate at no-load speed	0 – 44,800 bpm

Drilling range

Drilling diameter in wood	25 mm
Drilling diameter in steel	10 mm
Drilling diameter in masonry	15 mm

Noise/vibration information

Sound pressure level	97 dB(A)
Sound power level	108 dB(A)
Uncertainty K	5 dB

Sales information

Positioning

- Compact power – The most compact and powerful impact drill in its class

User benefit

- Robust and powerful 600 W motor
- Extremely handy: No bigger than a glove and 1.7 kg light
- Soft in line grip for a secure hold