

0 601 9F8 3F0 – GSB 180-LI

Material number	0 601 9F8 3F0
EAN	4059952576213
2 x battery GBA 18V 2.0Ah 1 600 A00 1CG	✓
Carrying case	✓
Quick charger GAL 18V-40 Professional 1 600 A01 9RM	✓



Technical data

Technical data

Torque (soft/hard/max.)	21/54/- Nm
No-load speed (1st gear / 2nd gear)	0 – 500 / 0 – 1,900 rpm
Battery type	Lithium-ion
Max. impact rate	27.000 bpm
Chuck capacity, min./max.	1.5 / 13 mm
Battery voltage	18.0 V
Torque settings	20+2
Tool dimensions (width)	62 mm
Tool dimensions (length)	210 mm
Tool dimensions (height)	225 mm
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 88 dB(A); Sound power level 99 dB(A). Uncertainty K= 5 dB.

Drilling diameter

Max. drilling diameter in wood	35 mm
Max. drilling diameter in steel	10 mm
Max. drilling diameter in masonry	10 mm

Screw diameter

Max. screw diameter	10 mm
---------------------	-------

Noise/vibration information

Sound pressure level	88 dB(A)
Sound power level	99 dB(A)
Uncertainty K	5 dB



Sales information

Positioning

- More power. More Robust.

User benefit

- Affordable: Bosch Quality at affordable price!
- Highly Serviceable: Motor has changeable carbon brushes for easy maintenance and serviceability!
- Durable: Designed with Robust Housing and Battery Cell Protection!